

# QPR Concrete Crack Filler



## Manufacturer:

QPR  
12735 Morris Rd Ste 150  
Alpharetta, GA 30004  
Phone: (866) 274-0935  
Fax: (678) 746-2238

## Description

Concrete Crack Sealant is a 100% acrylic elastomeric sealant designed for filling cracks up to 1/2" wide in concrete pavement surfaces.

## Uses

- Fills cracks up to 1/2" wide in concrete surfaces
- Seals out moisture

## Surface Preparation

Clean Cracks – Remove dirt and vegetation from cracks with screwdriver, wire brush or other suitable instrument. Flush out crack with water and allow to dry.

## Application

Apply QPR Concrete Crack Filler – Mix contents of container by moderately shaking. Cut top of spout to desired width (smaller than width of crack). Fill cracks and smooth flush to adjoining pavement with putty knife. Allow crack sealant to dry for 24 hours. If desired, a second application may be applied. Allow Crack Sealant to cure 24 hours before resuming traffic.

## Drying Time

Allow 24 hours depending on weather conditions.

## Clean Up

Clean application tools with water before material dries.

## Weather Conditions

Application temperature must be a minimum of 60°F and rising. Do not apply when temperature is expected to drop below 60°F within a 24 hour period. Be sure to wear eye protection when working with this product.

## Coverage (Approximate)

Coverage is dependent upon depth and width of cracks. Typically, one quart of Concrete Crack Sealant will fill approximately 20–35 feet of cracks.

## Precautions

- Do NOT freeze
- Do NOT store at temperatures below 50°F

## Safety and Environmental Precautions

- Refer to Material Data Safety Sheet before using
- Close container when not in use
- Environmental information is on the Material Data Safety Sheet
- Do not reuse empty container
- KEEP OUT OF REACH OF CHILDREN

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary
Silicon Dioxide	14808-60-7